



RPI-TL

12V DC TO 120VAC POWER INVERTER



- ✓ (16.6 milliseconds) Automatic Transfer to Battery-Derived AC Output
 - ✓ 750 Watts (continuous) / 1500 Watts (peak)
 - ✓ 3 Stage, 20 AMP Selectable Wet/Dry Battery Charger
 - ✓ Battery Monitoring
 - ✓ Overload Protection
 - ✓ AC Surge Suppression - 450 Joules
 - ✓ Limited 2 Year Warranty
- * Battery not included



www.ramsetinc.com

ADDITIONAL ACCESSORIES



LCD-Keypad

*1,024 Codes • 5,112 Event Log
LCD Display • 7-Day Timer
Time Zones • Latching/Hold Open
Stainless Steel Faceplate*



Magnetic Lock

*12/24V DC.
1,100 lb holding force.
Secures the gate(s) closed.*



ILD-24S Loop Detector

*Plug-in loop detector with
sensitivity adjustment and inherent
loop diagnostics.*



Uphill Arms

*1" X 2" rectangular 12 ga.
steel tubing anodized with
heavy duty ball joints
for flexibility.*



Post Mounts

*1/4" angle iron flats. 3/16" square
tubing legs. Used to mount the
operator off the ground.*



Goose Necks

*Square - 16 ga. Available in 48"
pad-mount or 66" in-ground.
Used for mounting keypads,
phone entry systems,
card readers...etc.*



Fire Box

*Allows the fire department to open
the gate in the case of
an emergency.*



BBS-Battery Back-Up System

*1,000 lb capacity. Opens the
gate when power is lost.*



Uphill Hinges

*Heavy duty hinges used for uphill
swing gate applications.*



Key Switch Box

*Suitable for use on entry doors
where access is restricted by a key.*



9116 De Garmo Ave.
Sun Valley, CA 91352

Tel: (800) 771-7055 • Fax: (818) 504-1141