

Accessories



Magnetic Lock
12/24V DC. 1100 lb holding force. Secures the gate(s) closed.



RLD-24 Loop Detector
A safety device that stops the gate from closing on a vehicle.



Chain Drop Box
Mechanical chain release fire box designed for use on sliding gates.



RAMSET Fire Box
Allows the fire department to open your gate in the case of an emergency.



BBS-Battery Back-Up System
1000 lb capacity. Opens the gate when power is lost.



Key Switch Box
Suitable for use on entry doors where access is restricted by a key.



Thru-Wall Extension
Extends drive sprocket & idlers thru-wall. Keeps operator inside property/ building.



Post Mounts
1/4" angle iron flats. 3/16" square tubing legs. Used to mount the operator off the ground.



Premium Guide Rollers
Heavy duty UHMW rollers. Lengths: 4", 6", 12" Colors: Black or White



Adjustable Guide Rollers
Heavy duty UHMW rollers adjust to fit any gate. Lengths: 4", 6", 12"



RPI (Ramset Power Inverter)
Maintains power to your operator and accessories when the main power is lost. 750W output.



Goose Necks
Square - 14 ga. Available in 48" padmount or 66" in-ground. Used for mounting keypads, phone entry systems, card readers...etc.



✓ Easy Installation

✓ Heavy Duty

✓ Reliable

✓ Low Maintenance



RAM 5000
Commercial Industrial



RAM 5100
Commercial Industrial



RAM 5200
Commercial Industrial



10-Year Warranty Residential	7-Year Warranty Commercial
-------------------------------------	-----------------------------------

DISTRIBUTED BY:

SPECIFICATIONS:

MAXIMUM GATE WEIGHT: 1000 lbs.
MAXIMUM GATE TRAVEL: 40'
GATE TRAVELING SPEED: Approx. 1' per sec.
CYCLES: Continuous. SHIPPING WEIGHT: 125 lbs.
OPERATING TEMPERATURE: -10° F to 160° F

Electric Motor:

1/2 Hp, 115 VAC. 4.5 amp 50/60Hz, continuous duty with high speed ball bearings and resettable overload button.

Heavy Duty Worm Gear:

Lubricated in an oil bath for smooth and quiet operation.

Limit Switches:

Mechanical adjustment for accurate gate stop settings.

Finish:


Gold/Zinc plated to inhibit corrosion.

Cover:

High-impact resistant charcoal gray polyethylene.

Cover Dimensions:

H: 25" L: 16 1/2" W: 18 1/2"



RAM 5000

Commercial / Industrial

SPECIFICATIONS:

MAXIMUM GATE WEIGHT: 2000 lbs.
MAXIMUM GATE TRAVEL: 40'
GATE TRAVELING SPEED: Approx. 1' per sec.
CYCLES: Continuous. SHIPPING WEIGHT: 125 lbs.
OPERATING TEMPERATURE: -10° F to 160° F

Electric Motor:

3/4 Hp, 115 VAC. 8.5 amp 50/60 Hz, continuous duty with high speed ball bearings and resettable overload button.

Heavy Duty Worm Gear:

Lubricated in an oil bath for smooth and quiet operation.

Limit Switches:

Mechanical adjustment for accurate gate stop settings.

Finish:


Gold/Zinc plated to inhibit corrosion.

Cover:

High-impact resistant charcoal gray polyethylene.

Cover Dimensions:

H: 25" L: 16 1/2" W: 18 1/2"



RAM 5100

Commercial / Industrial

SPECIFICATIONS:

MAXIMUM GATE WEIGHT: 3000 lbs.
MAXIMUM GATE TRAVEL: 40'
GATE TRAVELING SPEED: Approx. 1' per sec.
CYCLES: Continuous. SHIPPING WEIGHT: 125 lbs.
OPERATING TEMPERATURE: -10° F to 160° F

Electric Motor:

1 Hp, 230 VAC. 4.5 amp 50/60Hz, continuous duty with high speed ball bearings and resettable overload button.

Heavy Duty Worm Gear:

Lubricated in an oil bath for smooth and quiet operation.

Limit Switches:

Mechanical adjustment for accurate gate stop settings.

Finish:


Gold/Zinc plated to inhibit corrosion.

Cover:

High-impact resistant charcoal gray polyethylene.

Cover Dimensions:

H: 25" L: 16 1/2" W: 18 1/2"




RAM 5200

Commercial / Industrial

RAMSET "Intelligate" Control Board

UL 325 2016 Edition 6



The Intelligate control board is the most advanced gate controller in the industry, putting Ramset ahead of the competition when it comes to reliability and number of features. It is controlled by a programmable microprocessor that reads and precisely executes all functions of the control board. Some of the features of the control board:

- * Automatic close timer
- * Pre warning alarm relays
- * Constant warning alarm relays
- * Manual or self adjusting ERD
- * Dual gate communication capability
- * Secure close
- * Anti-tailgating/One pass system
- * Radio cycle (open, stop & close)
- * Open & close delays
- * Indicator lights for easy troubleshooting
- * Plug in loop detectors
- * Left/Right installation switch