



MADE IN THE USA ★★★★★	S L I D E						S W I N G							O V E R H E A D			S W I N G		S L I D E	
	Res/Commercial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Single Home	Res/Commercial	Res/Commercial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Com/Industrial	Res/Commercial	Res/Commercial	Res/Commercial
	RAM 100	RAM 1000	RAM 5500	RAM 5000	RAM 5100	RAM 5200	RAM 30	RAM 302	RAM 300	RAM 3000	RAM 3100	RAM 3200	RAM 30-30	RAM 2000	RAM 2100	RAM 2200	MODUS	JET	DYNAMOS	
Gate Travel/Weight:	20' /700 lbs	45' /1,000 lbs	45' /2,500 lbs	40' /1,000 lbs	40' /2,000 lbs	40' /3,000 lbs	12' /400 lbs	18' /800 lbs	18' /800 lbs	22' /1,000 lbs	22' /1,200 lbs	22' /1,400 lbs	20' /3,000 lbs	20' /450 lbs	20' /700 lbs	20' /700 lbs	14' /800 lbs	12' /800 lbs	30' /800 lbs	
Opening Speed:	1' /sec	1' /sec	1' /sec	1' /sec	1' /sec	1' /sec	90° /16 sec	90° /16 sec	90° /14 sec	90° /20 sec	90° /20 sec	90° /20 sec	90° /16 sec	90° /14 sec	90° /14 sec	90° /14 sec	90° /18 to 24 sec	90° /16 to 20 sec	10" /sec	
Cycles:	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	30 Cycles/Hr	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous	30 Cycles/Hr	40 Cycles/Hr	40 Cycles/Hr	
Motor:	1/2 Hp	1/2 Hp	1 Hp	1/2 Hp	3/4 Hp	1 Hp	1/2 Hp	1/2 Hp	1/2 Hp	1/2 Hp	3/4 Hp	1 Hp	3/4, 1 Hp	1/2 Hp	3/4 Hp	1 Hp	24 VDC	24 VDC	24 VDC	
Input Power:	120 VAC	120 VAC	110 VAC	120 VAC	120 VAC	220 VAC	120 VAC	120 VAC	120 VAC	120 VAC	120 VAC	220 VAC	120, 220 VAC	120 VAC	120 VAC	220 VAC	120 VAC / Solar	120 VAC / Solar	120 VAC / Solar	
Motor amps:	4.5 amp	4.5 amp	9.4 amp	4.5 amp	8.5 amp	4.5 amp	5.2 amp	4.5 amp	4.5 amp	4.5 amp	8.5 amp	4.5 amp	8.5/4.5 amp	4.5 amp	8.5 amp	4.5 amp	3 amp	3 amp	3 amp	
Hertz:	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	
Operating Temp:	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-4°F to 131°F	-4°F to 131°F	-4°F to 131°F
Height:	H 22"	H 26"	H 27"	H 25"	H 25"	H 25"	H 20"	H 16½"	H 27"	H 28½"	H 28½"	H 28½"	H 27½"	H 10"	H 10"	H 10"	H 13"	H 4"	H 17½"	
Length:	L 14½"	L 16"	L 16"	L 16½"	L 16½"	L 16½"	L 13½"	L 23"	L 16½"	L 18"	L 18"	L 18"	L 17½"	L 143"	L 143"	L 143"	L 6"	L 32"	L 16¼"	
Width:	W 15"	W 16½"	W 16½"	W 18½"	W 18½"	W 18½"	W 13½"	W 13½"	W 20"	W 23"	W 23"	W 23"	W 23½"	W 13"	W 13"	W 13"	W 10"	W 4"	W 10"	
Shipping Weight:	110 lbs	125 lbs	135 lbs	125 lbs	125 lbs	125 lbs	75 lbs	100 lbs	110 lbs	150 lbs	150 lbs	150 lbs	200 lbs	135 lbs	135 lbs	135 lbs	33 lbs	22 lbs	50 lbs	
Emergency Release:	Foot Pedal Release	Foot Pedal Release	Foot Pedal Release	Chain Release	Chain Release	Chain Release	Knob Release	Hand Lever	Foot Pedal Release	Hand Lever	Hand Lever	Hand Lever	Knob Release	Trolley Release	Trolley Release	Trolley Release	Key Release	Key Release	Key Release	
Battery Back Up System (optional)	RPI	BBS/RPI	RPI	BBS/RPI	BBS/RPI	BBS	RPI	BBS/RPI	BBS/RPI (requires removal of foot pedal release)	BBS/RPI	BBS/RPI	BBS	BBS	BBS/RPI	BBS/RPI	BBS	BBS	BBS	BBS	

<p>RPI (Ramset Power Inverter) Maintains power to your operator and accessories when the main power is lost. 750W output.</p>	<p>BBS-Battery Back-Up System 1000 lb capacity. Opens the gate when power is lost.</p>	<p>LCD-KP 1,024 codes. 5,112 event log. LCD display 7-day timer. Time Zones Latching. Stainless Steel Faceplate</p>	<p>ILD-24S Loop Detector Plug-in-loop detector with sensitivity adjustment and inherent loop diagnostics.</p>	<p>RAMSET Stylo Remotes & Receiver 4-Channel Radio Transmitter, Rolling Code, Small, Sleek, black and Chrome Design.</p>	<p>Magnetic Lock 12/24V DC. 1100 lb holding force. Secures the gate(s) closed.</p>	<p>RAMSET Fire Box Allows the fire department to open your gate in the case of an emergency.</p>	<p>Chain Drop Box Mechanical chain release fire box designed for use on sliding gates.</p>	<p>Key Switch Box Suitable for use on entry doors where access is restricted by a key.</p>	<p>Premium V Groove Wheels Solid steel and UHMW wheels. Size: 4" & 6" Colors: Black or White</p>	<p>Premium Guide Rollers Heavy duty UHMW rollers. Lengths: 4", 6", 12" Colors: Black or White</p>	<p>Adjustable Guide Rollers Heavy duty UHMW rollers adjust to fit any gate. Lengths: 4", 6", 12" Colors: Black or White</p>	<p>Goose Necks Square - 14 ga. Available in 48" padmount or 66" in-ground. Used for mounting keypads, phone entry systems, card readers...etc.</p>	<p>Post Mounts 1/4" angle iron flats. 3/16" square tubing legs. Used to mount the operator off the ground.</p>	<p>Uphill Hinges Heavy duty hinges used for uphill swing gate applications.</p>	<p>Uphill Arms 1" X 2" rectangular 12 ga. steel tubing anodized with heavy duty ball joints for flexibility.</p>
--	---	--	--	---	---	---	---	---	---	--	--	---	---	--	---